

CLAS12 Hydra

Data Emulation &
RG-L Statistics

Darren W. Upton



Hydra Team



David Lawrence

EPSCI
Physics, CS, AI/ML



Thomas Britton

EPSCI
Physics, CS, AI/ML



Torri Jeske

EPSCI
Operations + Full Stack



Natalia Matsiuk

Information + Records
Containerization, QA



Raiqa Rasool

EPSCI
CS, Full Stack Development



Darren Upton

ODU Physics Grad Student
Emulated images, clustering,
Siamese models



Jordan O'Kronley

UT Physics Graduate Student
Image clustering and siamese
models



Introduction to Hydra

❖ Monitoring Workflow


- Python-based modules handling image moving & ML workflow

❖ Back End

- SQL database communicates between front-end and back-end

❖ Front End

- Web-based UI for accessing info



Hydra - Run Page



News ↕

----- No News for now -----

Run Number: 22930 | Last Update: 9/8/2025 3:19:45 PM ⓘ





● Polling

Hidden Plots

■ Disregard ■ No Model ■ Good ■ Bad ■ NoData


PLOTS (82 / 82)

Filter Plots: Open Filter Options ▾



Hydra - Grafana Timeline

Alarm



Data Augmentation for Hydra

Data Augmentation

- ❖ Making new data from existing data
- ❖ Image data **rotated**, **cropped**, or **re-colored**
- ❖ Not **that** easy for CLAS12




Edgar




Emulating Failures

- ❖ Generate pseudo-data using existing data
- ❖ Create new version CCDB table with crates or slots “knocked-out”
- ❖ Run mon12 with only ECal for specific good run in RG-K

Crate 15




Crate 13, Slot 5



Iolaus

- ❖ Helped Heracles slay the Hydra by burning the neck stumps, preventing the heads from growing back
- ❖ Systematically perform knock-outs using CCDB tables & mon12





Results of First Pass

- ❖ I tested some models in-real time
 - (Sorry if you were confused on-shift)
- ❖ Improvements for occupancy plots
 - **Okay-ish** model generalization
- ❖ Not enough for **some plots**
- ❖ **What's causing this behavior?**




Checking with Unsupervised Clustering

- ❖ “Islands” cluster by target/beam not “good” or “bad”
- ❖ Generalization will require sampling multiple “islands”



Status of Iolaus

- ❖ Good progress for ECal emulation using previous and RG-L data
- ❖ Starting to move onto CTOF & DC




Hydra for RG-L

Overview of Hydra for RG-L


- ❖ Run Page showed 82 plots for RG-L
 - Starting with ~30 models
 - Up to ~65 models in production from lolaus & better labeling
- ❖ **Let's see two specific events where Hydra spotted issues!**

Hydra Case Study #1

- ❖ Hydra alarm upon return
 - Jumpy timeline
 - Hotspot





Hydra = Over-Engineered Light Detector




Hydra Case Study #2

- ❖ Chunk of ECAL sector 2 out **starting at 08:40** (lasted ~4.5 hours)
 - Caused by issues with HVECAL2 board 6
- ❖ Missed until Dan called at 10:40 because no monitor showing Hydra in counting house...



Compiling “Hydra Events”

- ❖ Instances where at least 1 Hydra model alarmed
- ❖ Broken down into three types
 - Quick (< 1 hour)
 - Reset with new run (1-2 hr)
 - Caught by non-shifters (>2 hr)
- ❖ **Analysis ongoing!**





Lessons from 2025


- ❖ **Hydra only helps when it stays up on a monitor**
- ❖ Emulation via lolaus can be performed once “good” runs exist
- ❖ Grafana timelines help spot small issues (even single hot pixel)

Moving Forward

- ❖ Use **Iolous** for the DC & other detectors without active models
 - Work with Florian to craft approach aided by clustering
- ❖ Continue collecting stats from previous run periods
 - Try using Will's project for an **LLM trained on CLAS12 log book**




Questions/Comments



Backup Slides



Clustering via Unsupervised Learning

- ❖ Map images into feature space using an ML model for images
- ❖ Apply k-means clustering to determine groups
- ❖ Reduce dimensionality using TSNE for visualization



Hydra Case Study #3

❖ Single hot pixel



Interpretability for Hydra


GradCAM Heat Maps

“Why did Hydra say this was bad?”




Bright spots indicate important regions of the image for the given classification.

These are very sensitive to how well the model is trained.

this is a normal image




this is a bad image




Heat maps are produced from mixed layers in InceptionV3+CBAM

Labeling Stats




Labelling Stats


Labeled vs Unlabeled Images by Detector System (Counts)




Distribution of Image Labels by Detector System (Percentage)



Model Performance Metrics



RGL-specific



All time performance on Bad images

Siamese Models

Siamese Models

Siamese models learn to compare two inputs (in our case images) and determine how *similar* they are.

Think of this as Hydra's equivalent to the shift crew comparing images to their reference.



Jordan O'Kronley

UT Physics Graduate Student
Image clustering and siamese
models

