

# Gradient Calibration

Jay Benesch

7/15/2015

# Goal

- Calibrate cavity gradients (aka field probe) at typical operating gradient with 3% RMS error
- With eight cavities in a module, adding in quadrature suggests the error of the sum will be  $\sim 1\%$ . This error will be placed in the quadrupoles by lem.
- Over the full linac, lem fudge factor alters all cavities as needed to get momentum in arc right but quads aren't changed. NL 4%, SL 1.6% recently
- 1% local optics error will improve fit to model over present conditions with large lem fudge factors and calibration errors – whether the improvement is worthwhile requires CASA analysis


# Old method

- Highest gradient cavity in linac as reference
- lem with that cavity at 3 MV/m (7 MV/m for C100)
- Record arc energy baseline
- Lower cavity under test to 3 MV/m while raising reference cavity (balance null measurement)
- Use energy lock system to record arc energy offsets from baseline; correct offline
- Limited by dp/p obtainable with 3 MV/m lower GSET value.
- Error set by RFCM stability and net drift in all other cavities during measurement
- Repeated measurements on single cavity test/reference pair ~ 5 MV/m in SL showed ~7% standard deviation

# Proposed method

- Use phase shifter, calibrated to  $0.1^\circ$  on the bench, to alter momentum due to test cavity
- Offsets from crest of  $165^\circ$  possible, so much more  $dp/p$  available even on poor cavities
- Two variations will be presented
- M15 BPMs  $\pm 6$  mm linear response within 4% error if beam starts centered, so high dispersion optics may be counterproductive
- Coding time may decide which of two options is chosen

# Arc 1 momentum stability



## Statistics Info

Channel	ARC1:p
Min	557.466
Max	557.593
Mean	557.537
rms	557.537
SDEV	0.014

$$\text{SDEV } 0.014/557.537 = 2.5\text{E-}05$$


$$\text{Half-span } \sim 0.07/557.537 \sim 1.25\text{E-}4$$

~18  $\mu\text{A}$  CW to hall A

Energy lock on per R1QXGMES behavior

15 of 25 zones on, so might decrease 20%

# Arc 2 momentum stability



ARC2:p

## Statistics Info

Channel	ARC2:p
Min	1056.886
Max	1057.043
Mean	1056.959
rms	1056.959
SDEV	0.020

SDEV  $0.020/1056.959 = 1.9E-5$



Half-span  $\sim 0.08/1057 \sim 8E-5$

$\sim 18$  mA CW to hall A

R2QXGMES indicates arc 2 energy lock on.




15 of 25 zones on, so might decrease 20%

# M15 error estimate



- Matlab simulation by John Musson
- Dimensions in mm, so first lighter band is 200 microns error
- Actual BPM is rotated  $45^\circ$  from model, so +X is towards corner
- If 3% location error desired, must keep X displacement under  $\sim 6$ mm
- With 7.5 m peak dispersion optics, 6 mm =  $dp/p$   $8E-4$ , too small given linac drifts
- 2.5 m dispersion yields  $2E-3$  at 5 mm excursion, OK if  $140 \mu\text{m}$  error ( $5.6E-5$ )

# Monte Carlo results – worst cavity



MC coded in ROOT by Luke Myers, Hall A  
1000 iterations of 3 MV/m (1.5 MeV) cavity  
assuming energy measurement error  $6E-5$   
and phase set error  $0.1$  degrees. Seven phase offsets  
equally spaced. RMS 0.08 of 1.5 MeV, 5.4%.  
Energy error includes  $5.6E-5$  from BPMs and  
 $2E-5$  from arc energy variation in quadrature.



# Pre-requisites

- Quad center all BPMs in 1A and 2A. If SOF is greater than 1 mm, consider turning off BPM. (1A33 2.5 mm)
- Install 2.5 m dispersion optics so  $dp/p \pm 2E-3$  can be obtained within good region of BPM and net drift of linac during measurement is less of an issue.
- Steer within 0.5 mm of (0,0) through arc
- Run Krest replacement Phaser on all cavities (8h).
- (option B) Absolute calibration of NL26 and SL26 cavities individually against arc (24h)




# Option A

- This option an extension of Phaser
- Adjust arc dipole bus so beam near  $x = 5$  mm
- Within  $4E-3$ , calculate maximum phase shift and two lower values, about equally spaced in  $\sin(\theta)$
- Energy lock off
- Measure energy at seven phases with BEM, as in Monte Carlo.  $\sim 3$  minutes
- Fit amplitude and phase of sine, including errors
- Restore cavity and repeat for each of 416. Four to five shifts total, given usual inefficiencies.
- Evaluate data offline. Apply to download files, CED.

# Option B




- Longer to code (6 weeks vs 2 weeks?)
- Needs energy lock cavity absolute calibration (one day)
- Calculate shifts for  $165^\circ$  (C25),  $120^\circ$  (C50) and  $75^\circ$  (C100) .
- For three phase shifts on either side of crest, download phase and energy lock offset calculated to keep beam centered if test cavity calibration already correct.
- Using applied energy lock offset and BEM reading of arc energy, calculate actual energy offset as function of phase
- Fit seven points to sine
- Data acquisition about twice as long, say three days (+1)
- Beam stays close to zero so BPM accuracy and linac stability in quadrature likely  $3E-5$  vs  $6E-5$  as in MC

# Monte Carlo: 6 MeV cavity



Sigmas used: energy  $6E-5$ , phase 0.1 degrees.

# Monte Carlo: 12 MeV cavity



Sigmas used: energy 6E-5, phase 0.1 degrees.

# Table of Monte Carlo results

MeV input to MC	Mean	RMS	RMS/mean
<b>1.5</b>	1.521	0.082	<b>5.4%</b>
<b>2</b>	2.018	0.087	<b>4.3%</b>
<b>2.5</b>	2.510	0.088	<b>3.5%</b>
3	3.010	0.089	3.0%
4.5	4.509	0.085	1.9%
6	6.005	0.130	2.2%
7.5	7.510	0.188	2.5%
9	9.023	0.231	2.6%
10.5	10.514	0.298	2.8%

Monte Carlo results for Gaussians with energy error sigma  $6E-5$  and phase error sigma 0.1 degrees, in arc 2 at 2303 MeV. Corresponds roughly to Option A. *3.2% max arc 1.*

# Conclusions

- It is possible to reach ~3% error per cavity as desired for all of NL and perhaps three-fourths of SL using phase shifter and Option A
- Option B provides a factor of two better accuracy than Option A, but takes a lot longer to code – perhaps too long for October 2015 testing and deployment given other HLA tasks
- Recommendation: ask HLA to code Option A. Allocate two four hour code testing periods and 4-5 shifts for measurement.
- $Q_0(E_{\text{typical}})$  should be measured for zone **after** gradient calibration and CED then adjusted for Cryo





# Monte Carlo results 1213 MeV

MeV input to MC	Mean	RMS	RMS/mean
1.5	1.507	0.046	3.1%
2	2.006	0.046	2.3%
2.5	2.501	0.047	1.9%
3	3.003	0.066	2.2%
4.5	4.511	0.123	2.7%
6	6.014	0.173	2.9%
7.5	7.508	0.242	3.2%
9	9.031	0.287	3.2%
10.5	10.513	0.318	3.0%

Monte Carlo results for Gaussians with E error sigma **6E-5** and phase error sigma 0.1 degrees, in arc 1 at 1213 MeV. If we have only one 2K cold box when calibration is done, these RMS errors would obtain for arc 2.

# Monte Carlo results 1213 MeV, 3E-5

MeV input to MC	Mean	RMS	RMS/mean
1.5	1.502	0.024	1.6%
2	2.001	0.023	1.1%
2.5	2.501	0.024	1.0%
3	3.001	0.033	1.1%
4.5	4.502	0.056	1.2%
6	6.001	0.086	1.4%
7.5	7.505	0.088	1.2%
9	9.009	0.130	1.4%
10.5	10.505	0.157	1.5%
12	12.002	0.177	1.5%

Monte Carlo results for Gaussians with E error sigma **3E-5** and phase error sigma 0.1 degrees, in arc 1 at 1213 MeV.

# Monte Carlo results 2303 MeV, 3E-5


MeV input to MC	Mean	RMS	RMS/mean
1.5	1.507	0.043	2.9%
2	2.007	0.045	2.3%
2.5	2.504	0.043	1.7%
3	3.004	0.044	1.5%
4.5	4.501	0.043	1.0%
6	6.003	0.065	1.1%
7.5	7.505	0.095	1.3%
9	9.007	0.119	1.3%
10.5	10.504	0.149	1.4%
12	11.997	0.176	1.5%

Monte Carlo results for Gaussians with E error sigma **3E-5** and phase error sigma 0.1 degrees, in arc 2 at 2303 MeV

# Probe Q: C25

## Distributions

### probeQ



### Quantiles

100.0%	maximum	1.97e+7
99.5%		1.96e+7
97.5%		1.85e+7
90.0%		1.65e+7
75.0%	quartile	1.54e+7
50.0%	median	1.46e+7
25.0%	quartile	1.37e+7
10.0%		1.3e+7
2.5%		1.18e+7
0.5%		1.04e+7
0.0%	minimum	1.02e+7

### Moments


Mean	14691701
Std Dev	1503001.7
Std Err Mean	96816.852
Upper 95% Mean	14882421
Lower 95% Mean	14500982
N	241

Specification **1.5E7 +/- 40%**  
met in original production

# Probe Q: C50

## Distributions

### probeQ



### Quantiles

100.0%	maximum	6.81e+7
99.5%		6.81e+7
97.5%		5.41e+7
90.0%		4.38e+7
75.0%	quartile	3.87e+7
50.0%	median	3.48e+7
25.0%	quartile	3.1e+7
10.0%		2.79e+7
2.5%		2.01e+7
0.5%		1.48e+7
0.0%	minimum	1.48e+7

### Moments

Mean	35433333
Std Dev	7479455.1
Std Err Mean	801881.75
Upper 95% Mean	37027421
Lower 95% Mean	33839245
N	87

Specification unknown. Change not coordinated with LLRF or Operations. Span broader than original production, **3.5E7 +/- 60%** plus one outlier. LLRF has had 3db attenuators on all cavities for ~15 years, so this change was counterproductive.

# Very long term

- Upgrade BPM electronics in arcs 1 and 2 to reduce position and therefore energy error
- Code and run Option B
- The last time we calibrated the cavities with beam and used the measurements was 1995, so goal for this is 2035 if JLab still exists.