

# $A_1^n$ Polarized $^3\text{He}$ cell production and characterization

## Peoplepower

- Huong Nguyen (Research Scientist)
- Vladimir Nelyubin (Senior Research Scientist)
- Sumudu Katugampola (Grad student - rising 6th year)
- Chris Jantzi (Grad student - rising 4th year)

Gordon D. Cates


June 2018 Collaboration Meeting



# Steps in cell production

- Fabrication of the cell itself - for us, this is mostly pressure-testing the thin glass end-windows.
- Filling the cells - a big production I won't say much about.
- Cell Characterization
  - Intrinsic lifetime
  - Maximum polarization
  - Pressure
  - Wall thicknesses
  - K/Rb ratio (D value)
- Timing - historically, we have produced target cells as quickly as one per two weeks, since one cell can be on the vacuum system while one is being tested. With a year before the run, producing 9 or 10 additional cells is quite realistic.


# Design of the Hall C convection target



Note that the pumping chamber extends from roughly 22.1cm to 31.1 cm above the center of the target chamber.




# First beam-ready production target: Savior



On the gas system prior to being filled.



# Polarization test of Savior




While not a full simulated beam test, this was nonetheless extremely encouraging.





# Cell Characterization

- Requires a scannable single frequency laser.
- Our Coherent 899-29 is just too old!
- We have obtained a new Toptica DL Pro, scannable from roughly 700 - 800 nm. Roughly 100 mW over our frequency range of interest.






# Quick proof of principle of laser's capabilities




At right, percent transmission of laser light through a D2 filter: meant to be a crude simulation of a pressure broadening curve.






# Next cell to be made



This cell was previously on our gas system, filled with a hybrid alkali mixture, but was then “dumped” to atmosphere. Our expectations are low on its performance, but we plan to fill it as a warmup for the next cell (just received from Mike Souza at Princeton).




# One highlight from $\kappa_0$ measurement



Comparison of averaged water signal with a single-shot signal.

# Water calibrations: the average of fits versus the fit of an average



We consistently see a difference up to several percent. I believe all previous water calibrations suffer from this systematic.



# Short-term status and plans

- A new batch of thin end windows have been pressure tested and are ready to be incorporated into target cells.
- The first target cell of "Batch #2", with the recently tested end windows, has been received and is ready for filling.
- We are doing some maintenance on our vacuum system prior to beginning the next set of fills.
- We expect our new laser system to be ready to do characterizations when the next cells are filled.
- We will have roughly 250 Watts of laser light for full-polarization tests, roughly twice what is needed for Stage-I target cells.







