



Achieving ultra-stable RF control for plasma acceleration at LNF-INFN

Advancements in RF stability at the SPARC_LAB facility


L. Piersanti, M. Bellaveglia, X. Fang, A. Gallo, R. Magnanimi, S. Quaglia, M. Scampati, G. Scarselletta, B. Serenellini, S. Tocci



SPARC_LAB facility at LNF



- » SPARC_LAB facility was born as an R&D facility to develop a high brightness e- photo-injector for SASE-FEL experiments
- » The installation at LNF began in 2004. The first tests on the RF gun and measurement of beam parameters started in 2006
- » Many experiments have been carried out over the years:
 - SASE and seeded FEL
 - Thomson back-scattering, THz radiation generation
 - Plasma focusing and acceleration (Particle Wake-Field Acceleration PWFA)






SPARC_LAB facility at LNF




Today SPARC_LAB is a multi-disciplinary experimental facility that combines:




Plasma acceleration experiments at LNF



Over the past decade, R&D has focused on plasma acceleration



Plasma acceleration experiment at SPARC_LAB: Energy gain > 30 MeV in 3 cm > 1 GV/m gradient!



First FEL lasing from plasma accelerated beam

nature


Free-electron lasing with compact beam-driven plasma wakefield accelerator

https://doi.org/10.1038/s41586-022-04589-1
Received: 11 June 2021
Accepted: 25 February 2022
Published online: 25 May 2022


© Check for updates

R. Pompili¹⁵³, D. Alesini¹, M. P. Anania¹, S. Arjmand¹, M. Behtouei¹, M. Bellaveglia¹, A. Biagioni¹, B. Buonomo¹, F. Cardelli¹, M. Carpanese², E. Chiadroni¹, A. Cianchi^{2,4,5}, G. Costa¹, A. Del Dotto¹, M. Del Glorno¹, F. Dipace¹, A. Doria², F. Hilppi², M. Galletti^{2,4,5}, L. Giannessi¹, A. Giriboni², P. Iovine⁶, V. Lollo¹, A. Mostacoi², F. Nguyen², M. Opromolla⁸, E. Di Palma², L. Pellegrino¹, A. Petralia², V. Petrillo⁸, L. Piersanti¹, O. Di Pirro¹, S. Romeo¹, A. Rossi⁸, J. Scifo¹, A. Selce², V. Shpakov¹, A. Stella¹, C. Vaccarezza¹, F. Villa¹, A. Zigler^{1,8} & M. Ferrario¹

Single-shot spectrum of FEL radiation at 830 nm



Exponential gain of FEL radiation energy




Courtesy of R. Pompili and M. Galletti

LNF future facility: EuPRAXIA@SPARC_LAB




European consortium of excellence labs, 2 sites selected for LWFA (ELI Prague) and PWFA (LNF-INFN)



LNF future facility

- 1 GeV electron linac with a plasma acceleration module to drive 2 FEL Lines:
 - ARIA (180 nm) recent funding from Regional Government through ERDF Eu Program
 - AQUA (water region, around 4 nm)
- » It includes a brand-new building and ancillary utilities
- » Major investment (≈130 M€) and flagship project of INFN-LNF
- » Technical Design Report in the approval phase (end of the year)
- » Building tender to be issued soon (hopefully Oct. 2025) exp. completion end of 2029





Courtesy of A. Falone

SPARC_LAB RF system history



The requirements on RF stability (especially EM field phase) tightened from < 2 ps (RF gun characterization) to < 10 fs (PWFA)

Multiple upgrades to RF and synchronization systems, to follow the evolution of the facility over the years:

- » Low noise RMO
- » Electronic phase shifters for RF stations working point fine tuning
- » New photocathode laser locking electronics
- » Low-drift cables for reference and RF signals distribution
- » Fast intra-pulse phase feedback (klystron phase stabilization within the 4.5 μs RF pulse)

In 2024 a huge RF upgrade took place: new RMO, new digital LLRF systems, R&D on intra-pulse phase feedback

- » Higher measurement resolution and lower noise floor
- » Push to the limit the klystron induced phase jitter (GOAL: < 10 fs rms)</p>

SPARC_LAB new LLRF rack



SPARC_LAB new LLRF system


INFN

Upgrade motivations:

- » Custom RMO degraded performance + support discontinued
- » LLRF front-end noise limited the achievable phase resolution (50 fs rms)
- » Signal acquisition with general purpose ADC non negligible fault rate
- » Fully analog system (w. connectorized components) no pulse shaping for beam induced effects compensation


New RMO and LLRF system – Instrumentation Technologies:

» Improved RMO stability (10 Hz-10 MHz integrated jitter: 20.5 fs @ 2.856 GHz)



- » Front-end: temperature stabilized, 16-bit ADC @ 119 MS/s, 5 MHz BW
- » Independent pulse-by-pulse A and Φ feedback, long term stability (24h): < 100 fs rms
- » Back-end: fully customizable pulse shape, analog VM driven by FPGA, 14-bit DAC, 16 MHz analog BW
- » New LLRF control system developed with EPICS (see next talk by B. Serenellini)
- » Required resolution:
 - Amplitude: < 0.1% rms</p>
 - Added phase jitter < 10 fs rms

Courtesy of B. Serenellini



Intra-pulse feedback motivation and evolution



Intra-pulse feedback v1


FEL experiments demanded major improvements in RF stability. First implementation adapted from CW circular machines phase feedback

Intra-pulse feedback v2

Prototype with larger BW, successfully tested [1] on SS modulator + klystron at SPARC_LAB



2008




2021

Requirement for improved RF stability

First PWFA experiment showed the need for phase jitter below a few tens of fs



2023



2024 - today

Boosting S-band stability with intra-pulse feedback v3

- New feedback electronics
- Red Pitaya integrated signal readout
- Remotely controlled feedback gain
- Slow loop to reduce phase transients
- Successfully tested on S-band PFN modulators + klystrons at SPARC_LAB

[1] L. Piersanti et al. Photonics 11 p.413 (2024)

Intra-pulse feedback v3

INFN

Upgrade motivations:


- RF phase comparison stage optimized (reduced sensitivity to variations in the LLRF drive level)
- Only one Red Pitaya ADC/DAC module used to achieve a more compact architecture
- Remote interface for feedback gain fine tuning from control room
- Prototype chassis 1:1 copy of working system -> easier deployment at SPARC LAB facility


System deployment at SPARC LAB:

- Prototype of S-band intra-pulse feedback v3 developed, validated in lab, and installed at SPARC LAB for beamline tests (late 2024 – early 2025)
- New electronics tested on both S-band RF stations driven by PFN modulators

Measurement description


- RF pulse phase evaluated averaging the waveform within a configurable window
- 30 consecutive pulses acquired (5 Hz rep. rate 6 seconds acquisition)
- Phase jitter quantified as the RMS of the 30-pulse dataset





Intra-pulse feedback v3 block diagram






Intra-pulse feedback v3 gain scan



Gain scan

- » For both RF plants, a fine scan of the feedback gain was performed
- » For each gain value 5 minutes of data acquisition were recorded and the average jitter computed
- » Both plants show wide regions were the jitter stays below the project stability limit

For EuPRAXIA@SPARC_LAB, the total jitter of the S-band RF plant should be < 20 fs RMS Including the reference distribution jitter (10 fs RMS, worst case), the klystron jitter should be < $\sqrt[2]{20^2 - 10^2} \approx 17.5$ fs RMS




» The same scan would have been much more time consuming in the previous releases (variable resistor in the RF chassis in the modulator hall)


Intra-pulse feedback v3 short-term measurements




Example of phase measurement with optimized gain

- » Comparable performance for both RF plants
- » Oscillations on klystron 2 still to be addressed (PI gain too high?)





RF power plant	Intra-pulse feedback release			
	v1	v2	v3	
Kly1 RMS jitter	≈ 70 fs	≈ 20 fs	≈ 15 fs	
Kly2 RMS jitter	≈ 100 fs	≈ 35 fs	≈ 15 fs	



Conclusions



- » RF stability is a key challenge for plasma acceleration experiments at INFN-LNF
- » After a major upgrade of the RF system, the sensitivity to phase and amplitude jitters has significantly improved, enhancing the quality of measurements performed during operation
- » In parallel, continuous R&D on intra-pulse phase feedback is being carried out to push the stability of the RF power plants to their limits
- » Currently, we have succeeded in reducing the klystron phase jitter from hundreds of femtoseconds down to 15 fs, effectively "transforming" old PFN modulators into state-of-the-art solid-state ones in terms of phase stability
- » Reaching the **10 fs limit** now seems feasible, pushing the feedback performance even further






Spares

SPARC LAB best 10 seconds...





Plasma acceleration experiments





Over the past decade, R&D has focused on plasma acceleration and beam focusing with plasma lenses-> EuPRAXIA@SPARC_LAB new LNF facility

Plasma characterization

A. Biagioni et al., JINST 11.08 (2016): C08003

Focusing with active-plasma lenses






R. Pompili et al., PRL 121.17 (2018): 174801

R. Pompili et al., Appl. Phys. Lett. 110.10 (2017): 104101

Plasma acceleration




First plasma acceleration at SPARC_LAB: Energy gain = 4 MeV in 3 cm (133 MV/m)



Energy spread minimization in a beam-driven plasma wakefield accelerator

R. Pompili o 150, D. Alesini', M. P. Anania 1 M. Behtouei', M. Bellaveglia', A. Biagioni', F. G. Bisesto', M. Cesarini 1512, E. Chiadroni', A. Cianchi', G. Costa', M. Croia', A. Del Dotto 1. D. Di Giovenale', M. Diomede', F. Dipace 7, M. Ferrario', A. Giribono 1, V. Lollo', L. Magnisi', M. Marongiu 1, A. Mostacci 2, L. Piersanti 1, G. Di Pirro', S. Romeo', A. R. Rossi', J. Scifo', V. Shpakov', C. Vaccarezza', F. Villa 1 and A. Zigler^{1,5}

Second plasma acceleration experiment at SPARC_LAB: Energy gain > 30 MeV in 3 cm > 1 GV/m gradient!!!




Courtesy of R. Pompili and A. Giribono

First FEL lasing from plasma acceleration




Over the past decade, R&D has focused on plasma acceleration and beam focusing with plasma lenses-> EuPRAXIA@SPARC_LAB new LNF facility


SASE-FEL driven by PWFA beam



Single-shot spectrum of SASE FEL radiation at 830 nm




Exponential gain of FEL radiation energy





First FEL lasing from PWFA



Seeded FEL driven by PWFA beam







PHYSICAL REVIEW LETTERS

Stable Operation of a Free-Electron Laser Driven by a Plasma Accelerator

M. Gallettl et al.

Phys. Rev. Lett. 129, 234801 – Published 29 November 2022

Courtesy of R. Pompili and M. Galletti

Plasma synchronization: why we need fs stability



Fluctuations in the arrival time of electrons in the plasma reduce the efficiency of acceleration


 $\lambda_{\scriptscriptstyle P}\cong$ 300 μ m $f_{\scriptscriptstyle P}$ = 1 THz (RF equivalent)1 deg @ 1 THz \cong **3 fs**


Unfortunately the key parameter for controlling the beam arrival time on the plasma time scale is the stability of the 3 GHz RF!

1° rms jitter in the plasma corresponds to $\cong 0.003^\circ$ rms at 3 GHz For RF structures at 3 GHz the state of the art phase jitter is 0.01-0.02° rms

R&D on multiple fronts:

- » Reducing RF klystron jitter (intra-pulse feedback)
- » Reducing RF-laser relative jitter
- » Improving LLRF systems measurement sensitivity






Intra-pulse feedback v2 long-term measurements



Long-term stability measurements – April 2025


- » Before deploying new feedback release, 8 hours stability measurements were conducted
- » Drifts are minimized by slow feedback system
- » Measured values are coherent with measurement uncertainty +/- 1.5 fs
- » Overall larger jitter of line 2 due to non-optimized gain (manual variable resistor)
- » The lack of remote gain control makes the optimization process time-consuming and nearly impractical during operation



SPARC_LAB consolidation: the SABINA project



- » In 2019 a 6.1 M€ regional project (SABINA Source of Advanced Beam Imaging for Novel Applications) has been funded to consolidate the SPARC_LAB linac
- » The RF systems involved in this machine refurbishment are:
 - 3x digital LLRF systems: 2x S-band, 1x C-band (ITech)
 - 1x RMO (ITech)
 - ifficulties with current manufacturer (potential issue in case of HW faults)
 - 1x C-band Solid State modulator (ScandiNova)
- » New temperature stabilized LLRF rack in the SPARC bunker:
 - 3x LLRF systems
 - RF reference distribution from PC laser oscillator pulses








Expected SASE FEL performances



Radiation Parameter	Unit	PWFA	Full X-band
Radiation Wavelength	nm	3-4	4
Photons per Pulse	× 10 ¹²	0.1- 0.25	1
Photon Bandwith	%	0.1	0.5
Undulator Area Length	m	30	
ρ (1D/3D)	$\times 10^{-3}$	2	2
	mm ² mrad bw(0.1%)		$\begin{array}{c} 1 \\ \times 10^{27} \end{array}$

Electron Beam Parameter	Unit	PWFA	Full X- band
Electron Energy	GeV	1-1.2	1
Bunch Charge	рC	30-50	200- <i>500</i>
Peak Current	kA	1-2	1-2
RMS Energy Spread	%	0.1	0.1
RMS Bunch Length	μ m	6-3	24-20
RMS norm. Emittance	μ m	1	1
Slice Energy Spread	%	≤0.05	≤0.05
Slice norm Emittance	mm- mrad	0.5	0.5

In the energy region between Oxygen and Carbon K-edge 2.34 nm – 4.4 nm (530 eV -280 eV) water is almost transparent to radiation while nitrogen and carbon are absorbing (and scattering)



Coherent Imaging of biological samples protein clusters, VIRUSES and cells living in their native state

Possibility to study dynamics

~10 11 photons/pulse needed

Courtesy F. Stellato (UniTov)

Courtesy C. Vaccarezza


L. Piersanti – INFN-LNF



EUPRAXIA@SPARC_LAB: a high brightness PWFA



The accelerator is based on the combination of a <u>high brightness RF injector</u> and a <u>plasma</u>




L. Piersanti – INFN-LNF







World's Most Compact RF Linac: X Band





	Valu	Value	
PARAMETER	with linear	w/o	
	tapering	tapering	
Frequency [GHz]	11.99	11.9942	
Average acc. gradient [MV/m]	60	60	
Structures per module	2	2	
Iris radius a [mm]	3.85-3.15	3.5	
Tapering angle [deg]	0.04	0	
Struct. length L _s act. Length (flange-to-flange) [m]	0.94 (1	0.94 (1.05)	
No. of cells	112	112	
Shunt impedance R [MΩ/m]	93-107	100	
Effective shunt Imp. $R_{sh\ eff}$ [M Ω /m]	350	347	
Peak input power per structure [MW]	70	70	
Input power averaged over the pulse [MW]	51	51	
Average dissipated power [kW]	1		
P _{out} /P _{in} [%]	25	25	
Filling time [ns]	130	130	
Peak Modified Poynting Vector [W/µm²]	3.6	4.3	
Peak surface electric field [MV/m]	160	190	
Unloaded SLED/BOC Q-factor Q ₀	1500	150000	
External SLED/BOC Q-factor Q _E	21300	20700	
Required Kly power per module [MW]	20	20	
RF pulse [μs]	1.5	1.5	
Rep. Rate [Hz]	100	100	





Courtesy D. Alesini, F. Cardelli

L. Piersanti – INFN-LNF





Radiation Generation: FEL



Two FEL lines:


1) AQUA: Soft-X ray SASE FEL – Water window optimized for 4 nm (baseline)





First SABINA undulator in FRASCATI March 29, 2023

2) ARIA: VUV seeded HGHG FEL beamline for gas phase



SEEDED FEL – Modulator 3 m + 4 Radiators APPLE II – variable pol. 2.2 m each – SEEDED in the range 290 – 430 nm (see former presentation to the committee and *Villa et al. ARIA—A VUV Beamline for EuPRAXIA@SPARC_LAB. Condens. Matter 2022, 7, 11.*) – Undulator based on consolidated technology.





Courtesy L. Giannessi