
Measuring the Weak Charge of the Electron: The MOLLER Experiment

November 12, 2025

Kent Paschke





A Search for New Physics using Precision at Low Energies

Low energy measurements offer complementary probes of new physics at multi-TeV scales

EDM, g_{μ} -2, weak decays, β decay, $0\nu\beta\beta$ decay, DM, CLFV...

Parity-Violating Electron Scattering: Low energy weak neutral current couplings (SLAC, Jefferson Lab, Mainz)

 $A_{PV} \sim 32 ppb$

$$\delta(A_{PV}) \sim 0.8 \text{ ppb}$$

$$\delta(Q^{e_{W}}) = \pm 2.1 \% \text{ (stat.)} \pm 1.1 \% \text{ (syst.)}$$

Search for new flavor diagonal neutral currents

Unique (purely leptonic) new physics reach

Best Collider $\delta(\sin^2\theta_W)$:

A_I(SLD): 0.00026

A_{fb}(LEP): 0.00029

CMS(prelim): 0.00031

MOLLER projected:

$$\delta(\sin^2\theta_W) = \pm 0.00024 \text{ (stat.)} \pm 0.00013 \text{ (syst.)}$$

 $\sim 0.1\%$ Matches best collider (Z-pole) measurement

Best contact interaction reach for leptons at low OR high energy

To do better for a 4-lepton contact interaction would require the Giga-Z factory, linear collider, neutrino factory or muon collider

MOLLER Reach $\Lambda_{
m RR-LL}^{
m ee} \sim 38 \,\, {
m TeV}$

Erler et al., Ann. Rev. Nucl. Part. Sci. (2014)

MOLLER

 $A_{PV} \sim 32$ ppb with goal of 2% statistical, 1% systematic uncertainty

High luminosity and optimized acceptance

Møller Rate ~ 130 GHz

• signal = 1/3000 of beam electrons

Control Noise 91 ppm at 960 Hz

Integrate time


• 344 beam days (~3-4 calendar years)

Controlling Systematic Uncertainty

• calibration better than 0.4 ppb

JLab: precision instrument with 25 years of high precision PVES experiments

MOLLER collaboration: 40+years of experience including E158, Qweak, PREX/CREX




Parity Violating Electron Scattering: Probe of Weak Interaction


Parity Transformation

Parity transformation

$$x, y, z \rightarrow -x, -y, -z$$

$$\vec{p} \rightarrow -\vec{p}, \quad \vec{L} \rightarrow \vec{L}, \quad \vec{S} \rightarrow \vec{S}$$






Parity transformation is analogous to reflection in a mirror:


- . . . reverses momentum but preserves angular momentum
- ...takes right-handed (helicity = +1) to left-handed (helicity = -1).







Cavalier QB Chandler Morris







Weak interaction violates mirror symmetry



$$A_{PV} = \frac{\sigma_R - \sigma_L}{\sigma_R + \sigma_L} \sim \frac{\frac{Z^0}{|\mathcal{M}_Z|}}{|\mathcal{M}_{\gamma}|} \propto \frac{|\mathcal{M}_Z|}{|\mathcal{M}_{\gamma}|}$$


Scattering cross-section
$$\sigma = \left| \mathcal{M}_{\gamma} + \mathcal{M}_{Z} \right|^{2}$$

Well understood within the Electroweak Standard Model

- interference of electromagnetic and weak amplitudes
- known values for electron & quark weak neutral current coupling

But new physics could *also* appear here - too ephemeral to be seen directly, but contributing in a similar way here, slightly modifying this asymmetry from the Standard Model expectation

Electron Scattering and Parity-violation




right-handed incident electron

left-handed incident electron

- Incident beam is longitudinally polarized
- Change sign of longitudinal polarization
- Measure fractional rate difference

Identical particles $(e^-e^- \rightarrow e^-e^-)$


Boosted to Lab Frame



Measuring Apv

Goal: 10-8 asymmetry measurement at the few percent level

How do you pick a tiny signal out of a noisy environment?



Measure fractional rate difference between opposing helicity states

$$A_{PV} = \frac{\sigma_R - \sigma_L}{\sigma_R + \sigma_R}$$

 $A_{\rm measured} \sim$ -35 ppb with 2% precision N \sim 2.5x10¹⁸ electrons!

High rates to get statistical precision, but also:

Control Noise - quiet electronics, stability


Low backgrounds

Polarimetry


Kinematics

False Asymmetries - electronics, beam motion


Measuring Apv




Integration of detector current




Rapid (1kHz) measurement over helicity reversals






The Entire Accelerator Complex is our Apparatus



- Polarized Source Laser rapid reversal, keep spin states the same intensity, position, shape...
- Spin Manipulation crossed E and B fields, to rotate spin in low energy injector
- Position/Energy Modulation for calibrating detector sensitivity
- Polarimeters
- Precise monitors for beam current and position
- High luminosity Targets
- Spectrometers for isolating signal from background
- Detectors and data acquisition for low noise measurement
- RF accelerator for precise, low noise, stable, well-understood accelerated beam


Progress in PVeS studies




Broad program studying the structure of protons and nuclei, and searching for new physics

MOLLER apparatus

Polarized Electrons for MOLLER





Average beam asymmetry between polarization states must be small Goals: < 10 parts per billion intensity, < 6 Angstroms position difference

Beam generation and delivery must be low noise and no asymmetry between polarization states

- High intensity, high polarization through photoemission from GaAs photocathode
- Rapid-flip of beam helicity by reversing laser polarization with Pockels cell
- Beam must look the same for the two polarization states
- Photocathode has preferred axis: analyzing power for linear light source of <u>asymmetry!</u>
- In addition to avoiding asymmetry, <u>noise</u> is crucial to keep low in order to average down to 6 Angstroms!




CEBAF at JLab

Superconducting, continuous wave, recirculating linac


1500 MHz RF, with 3 interleaved 500 MHz beams



Superconducting RF is makes a clean, quiet beam... perfect for precision experiments




MOLLER in Hall A






MOLLER Spectrometer



Spectrometer Components

































Frame Weldment


TM1 Complete


Detector package


Primary A_{PV} measurement uses an array of thin quartz detectors

• 224 tiles total, over in 6 rings











Tracking chambers for calibration at 100,000x lower beam current (0.6 nA)

LH₂ Target

- •4.5 kW target power, 3.3 kW beam power
- •1.25m long LH₂ volume
- VERY stable!
 - density loss $\Delta \rho / \rho < 1\%$
 - density fluctuations $\delta \rho / \rho < 30 \text{ ppm}$





Position [m]

Flow outlet

Flow inlet

209e+00

How MOLLER Challenges SRF Performance

Robust, Stable Operation

The MOLLER apparatus requires time to stabilize after a beam interruption

- Accelerator recovery time: 0.5-few minutes
- •Beam ramp time: ~0.5 minutes, part of target protection
- Target thermal modulates with $\sim\!2K$ amplitude, $\sim\!1$ minute to stabilize
- Detectors thermal changes in photocathode resistivity, ~1 minute at full signal to stabilize

High duty factor requires very few trips. Goal: <6 trips per hour (20% loss of efficiency)

Beam trips related to SRF cavities

- Cavity trip
- Transient instabilities in cavities can deflect the beam (either transverse motion or in dispersive region due to energy change), triggering Beam Loss Monitor trips




Gradient Stability

MOLLER is highly sensitive to energy drifts due to g-2 spin precession of polarization A physics scattering asymmetry associated with transverse polarization creates a left-right asymmetry \sim 300 times larger than A_{PV}

1 MeV (about 1 part in 10,000) would be 2° spin precession \rightarrow false asymmetry 10x A_{PV} This would require correction.

Goal: <1° average precession change per day, so 5e-5 stability in beam energy. Energy locks will be used to control this, but stable operation makes this easier.


Average transverse asymmetry



Other (possible) SRF-related Challenges

Microphonics in RF cavity

- noise at 10Hz and harmonics, adding to random beam noise
- Appears to dominate noise frequency spectrum, but it isn't clear if this is critical after the MOLLER data collection "box-car" averaging



Field emission in cavities

- Some indication that this can create "stray" current electrons accelerated along with the bunches from the polarized source
- This would create poorly behaved halo even in high-current mode, produce excess beam in low beam current calibration mode





Summary

MOLLER, designed for ultra-high precision, will search for new interactions from 100 MeV to 10s of TeV, with reach into new physics phase space that cannot otherwise be accessed.

MOLLER is being assembled right now, and will begin running early 2027

Stable RF operation is critical for the efficient execution of experiment






thin quartz assembly modules in cosmic test stand



Detectors / electronics

Main detector assembly in Mainz test beam



shower-max detector



low-noise electronics (Manitoba)









VIZZ VIRGINIA TECH.

LAM

Beam pipe elements











Bellows 1 and 2

Bellows 3

Bellows 4

Bellows 5

Bellows 7











SAM Pipe





