

Overview of Enge Update

The University of Tokyo

Sho Nagao


on behalf of
JLab hypernuclear collaboration

Contents

- Experimental Overview
- Comments from ERR
- Updates

Drawing, SciFi, Simulation

E12-20-013A/E12-15-008A --Decay Pion Spectroscopy--



$(e, e' K^+)$ Experiments

" e' , K^+ " coincidence with HES & HKS
g.s & e.x B_A up to $A=6 \sim 208$
with <100 keV accuracy





Simultaneous data taking

Decay Pion Experiment


" π^- , K^+ " coincidence with Enge & HKS
g.s B_A of s-, p-, (sd-) shell
with a few 10 keV accuracy

Decay Pion Spectroscopy




A powerful tool for measuring hypernuclear ground-state energies thanks to excellent resolution
(World-leading resolution & precision for hyper-hydrogen peaks)

MAMI




Physics Impact

MAMI




- New determination of B_Λ with ~10 times better accuracy accuracy has led to further discussion of the ΛN interaction and strange nuclear matter.
- (By-product) Hypernuclear studies via lifetime and spin-parity measurements.

JLab (Li target)



JLab (Graphite target)



Pion Spectrometer --Enge--

Central Momentum	110 MeV/c
Momentum acceptance	78 ~ 140 MeV/c
Dispersion	1.53 cm/(MeV/c)
Momentum Resolution	10^{-3} (FWHM)
Solid Angle	4 msr

$\Delta p/p \sim 10^{-3}$ momentum resolution

Peak separation, Better S/N

Momentum from focal-plane position

Angular information for target reconstruction

A few 10 keV/c momentum calibration

With alpha-sources (~ 100 MeV/c/q) @target

Detect α particles with well-known momenta at the focal plane (in vacuum).


Target timing reconstruction: $\sigma \approx 100$ ps

Suppression of accidental coincidence background

Particle identification (π / μ / e)

Lifetime measurement

→ Requires a good start-time counter ($\sigma \approx 100$ ps) and position/angle measurements ($\sigma \approx 350$ μ m, 6.7 mrad).



alpha-source

Commercial α sources are available from "Eckert & Ziegler"

Procure an AF-type mixed 3-nuclide source via RadCon

^{230}Th , ^{241}Am , ^{244}Cm (1~5 kBq each)

Active diameter: 5 mm (no window)

<20 keV resolution (FWHM)

Removable package

\$3,610, Lead time: 5–6 weeks

Make special holder to mount to target ladder
and **1x5 mm² slit** to make small source point






Figure 38-A: Type PM Disk

A5504



Expected alpha-source result





Comments from the previous ERR

- **Finalize the location and shielding configuration** for electronics in the hall.
- Develop a realistic plan for shielding the **SiPMs from radiation damage**.
- **The effect of the PCS magnet's stray field** on the ENGE optics needs to be investigated.
- Alpha-source calibration with PCS magnets ON and OFF should be evaluated. Polarity reversal may change calibration, and possible nonlinear effects on calibration from polarity reversal should be evaluated. **An NMR probe should be installed** to better track the magnetic field.


Mechanical Drawing with Shielding

Drawing by Engineering Group




Enge Drawing Update


Previous ERR



Latest Version



Enge Detector Setup



TOF counter

Timing measurement & Trigger Timing

Two layers of plastic scintillator paddles

Re-assembling scintillators at ESB

Performance evaluation is ongoing ($\sigma_{\text{TOF}} \sim 200 \text{ ps}$)

by Kotaro

Drift Chamber

Tracking for target reconstruction

Employing HKS Drift Chamber

Evaluation with cosmic-ray data

by Ravindu & Ken

Scintillating Fiber Detector at Focal Plane

$\Phi 1\text{mm}$ Sci-Fi in vacuum (1000 ch)

Employing Outer-Layer-Scintillating (OSL) Fiber

67 keV/c LSB




Multi-Anode PMT as photon counter

Wide momentum coverage (78 ~ 140 MeV/c)



Fibers & PMT test with β -source $^{90}\text{Sr}/^{90}\text{Y}$

Update for Sci-Fi detector at Focal Plane (New Fiber)

Sci-Fi frame with fibers




ADC histogram




Update for Sci-Fi detector at Focal Plane (Radiation Issue)

High radiation level at Enge




	HES [rem/h]	HKS [rem/h]	Enge [rem/h]	Power Supply [rem/h]
r	0.080	0.033	0.60	0.048
e^\pm	0.49	0.43	5.6	Talked by Jin
n	0.020	0.000014	0.11	
Total	0.59	0.47	6.3	0.42

Before





After 20 mrem



After 20 mrem dose (3 hours for Pb target.),
SiPM degradation is observed




After 320 mrem dose (2 days),
Leakage current increased to 240 μA (from $< 10 \mu\text{A}$)
TDC peak efficiency dropped to a few tens of percent
→ Changed plan for stable operation.

From SiPMs to MA-PMTs



	SiPM (Hamamatsu MPPC)	Multi-Anode PMT (Hamamatsu H7546)
Single Photon Efficiency	~40%	~20%
Dark count rate	>1000 k / sec	20 k / sec
Gain	1.7×10^6	5×10^5
in Vacuum / in Mag. Field	○ / ○	✗ / ✗
Temperature Depend	✗	○
Radiation Damage	✗	○

OLD configuration



Frame

Fiber


Analog out,
Thermal, Bias
40pin
coaxial

MPPC board

+60 V for Bias (common bias for 64 ch)



Signal port
on chamber



Analog out,
Thermal
34pin
Flat cable




EASIROC Module on or under the platform
64 ch x 13 modules


LVDS out
34 pin
Flat Cable

VETROC LR-TDC
@ SHMS

New configuration with MA-PMT



Enge Detector Setup with Particle Trajectories



Dependence on production position
(Geant4 + TOSCA field map)

	X	Z
Resolution Deterioration (keV/mm)	~2	<1
Dispersion Changes (%/mm)	0.02	0.01
Focusing Position Shift (keV/mm)	40	13

Shifts in the production point have a non-negligible impact







- Beam position monitor with $\sigma \sim 100 \mu\text{m}$
- Beam- α -source relative position is known to within $100 \mu\text{m}$

PCS stray field has $\sim 0.08\%$ effect.
→ Non-negligible effect (90 keV/c shifts)



Summary

- Run-group experiment "Decay pion spectroscopy" with HKS-Enge simultaneous experiment with (e,e'K⁺)
- **Comments on the previous ERR**
 - Finalize the location and shielding configuration for electronics in the hall.
→ **Updating detector & shielding configuration**
 - Develop a realistic plan for shielding the SiPMs from radiation damage.
→ **MA-PMTs instead of SiPMs**
 - The effect of the PCS magnet's stray field on the ENGE optics needs to be investigated.
→ **Alpha-source calibration with PCS magnets ON/OFF is necessary. PCS magnet 10% deviation is acceptable for Enge calibration.**
- **Other Status**
 - TOF counter & Drift Chamber Tests are ongoing with cosmic rays at ESB (by May 2026)
 - Checked new Sci-Fi detector performance with β- and α-sources
 - Detailed design of vacuum port (by May 2026)
 - Sci-Fi small version with MA-PMT & NINO board (by May 2026)


Beam Position Shift Evaluation (by G4)



Lifetime measurement (by product)




K^+ time = Generate time




π^- time = Decay time

Possibility of Spin Assignment



[T.Motoba, NPA489 (1988) 683.]



[FINUDA, PLB681 (2009) 139.]

Spin-Parity assignment only for several hypernuclear ground-state

Possibility of spin inversion of the ground state in neutron-rich hypernuclei

Weak-decay branching-ratio depending on the spin-parity relationship of parent hypernucleus and daughter nucleus

→ spin-parity determination from weak decay branching-ratio

FINUDA exp. has determined spin-parity for several hypernuclei

[FINUDA, PLB681 (2009) 139]

[FINUDA, NPA881 (2012) 322]