

JLab Hypernuclear Collaboration 2026, Newport News, US
<https://indico.jlab.org/event/985/>

Thermal simulation for HKS target by ANSYS

Graduate School of Science, Kyoto University

Kei Ishido

February 13, 2026

Target list


Material	Thickness (mg/cm ²)	Density (mg/cm ³)	Beam current (μA)
⁶ Li	100	0.534	50
⁹ Be	100	1.848	50
¹¹ B	100	2.340	50
²⁷ Al	150	2.70	50
⁴⁰ Ca	150	1.55	50
⁴⁸ Ca	150	1.55	50
²⁰⁸ Pb	150	11.342	25
¹² C	150	1.750	50
¹² C hall	150	1.750	50
LiH	450/150/100	0.820	50
H ₂ O	-	1.00	-
CH ₂	450	0.930	2

Experiment target

Calibration target





Purpose and calculation flow



Energy deposit simulation by Geant4

Simulation set up




Energy deposit by Geant4 MC simulation

Material	CH ₂	⁶ Li	⁹ Be	¹¹ B	¹² C	²⁷ Al	⁴⁰ Ca	⁴⁸ Ca	²⁰⁸ Pb
Thickness (mg/cm ²)	450	100	100		150				150
Energy deposit (mean value) (MeV)	0.86	0.16	0.14	0.14	0.24	0.22	0.24	0.20	0.18
Beam current (μA)	2	50	50						25
Energy deposit (W)	1.7	8.3	7.1	7.2	12	11	12	10	4.5

Raster ON

Thermal simulation by ANSYS




Thermal conductivity between target and ladder frame: 100 W/(m · K)

Heating body($\phi = 100\mu\text{m}$ / Raster= $2 \times 2\text{mm}^2$)

Thermal simulation results (ANSYS)

Material	CH ₂	⁶ Li	⁹ Be	¹¹ B	¹² C	²⁷ Al	⁴⁰ Ca	⁴⁸ Ca
Max Temp(K)	296	22.6	45.6	51.4	478	88.2	111	291
Melting point (K)	398	453	1560	2349	3823	933	1115	601




Success of thermal calculations for simple models

➔ Next: more realistic simulations




Investigation of Lithium hydride(LiH) target



- density: 0.82g/cm³
- beam current: 50μA
- thermal conductivity: 10 W/(m·K)
- contact thermal conductivity: 100 W/(m · K)
- w/o raster or with raster
- melting point: 950K

LiH : Thermal simulation result



Summary & outlook

Thermal simulation of the targets

- Three tools
 - Geant4 (Energy deposit)
 - 3D-CAD software (design)
 - ANSYS (temperature)
- I have successfully gone through entire simulation flow



Outlook

- More realistic design will be incorporated in the simulation, cooperating with the target (David Meekins+) and designer teams
- Monte Carlo simulations for evaluating the effect on missing mass measurement from target design (thickness uncertainty / uniformity etc.) (in progress)

Back up



Ladder model for ANSYS simulation



Ladder model for ANSYS simulation

